

Safety Data Sheet NAILX Non Acetone Remover



NAILX

SDS Date: 10/08/2018

SECTION 1. IDENTIFICATION

Product Name: Non Acetone Nail Polish Remover
Packager: NailX Beauty Supplies, 5/201 Opawa Road
Emergency telephone number 021 286 4077
Recommended uses - Nail Polish Remover
Prepared by Karen Clark

SECTION 2. HAZARDS IDENTIFICATION

HSNO Hazard Classification: 3.1B, 6.1E, 6.4A, 6.9B
Refer to www.epa.govt.nz for Controls for this substance.

Signal word: DANGER

Hazard Statements

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H316 Causes mild skin irritation.
- H319 Causes serious eye irritation.
- H432 Toxic to terrestrial vertebrates.

Prevention Statements

- P102 Keep out of reach of children.
- P103 Read label before use.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash hands thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P273 Avoid release to the environment.
- P280 Wear protective gloves and protective eye/face protection.

Response Statements

P101 If medical advice is needed, have product container or label at hand.
P301 + P310 IF SWALLOWED: immediately call a POISON CENTRE or doctor.
P330 Rinse mouth. P331 Do NOT induce vomiting.
P303 + P361 + P352 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with plenty of soap and water.
P332 + P313 If skin irritation occurs: Get medical advice.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice.
P370 + P378 In case of fire: Use foam, dry chemical or carbon dioxide (CO₂).
P391 Collect spillage. Storage Statement
P403 + P235 Store in well-ventilated place. Keep cool.
P405 Store locked up. Disposal Statement
P501 Dispose of product to a landfill in accordance with any local regulations.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ethyl Acetate (AS# 141-78-6UN1173) OSHA PEL: 400 ppm
Isopropyl Alcohol (AS# 67-63-OUN1719 OSHA PEL: 400 ppm)

Non-Acetone Nail Polish Remover
Flammable liquid
Ethyl Acetate: 82.55% by volume
Isopropyl Alcohol: 13.00% by volume
Water 4.45% by volume

SECTION 4. FIRST AID MEASURES

Consult the National Poisons Centre, telephone 0800 764 766 [0800 POISON] or a doctor in every case of suspected poisoning. If medical advice is needed, have product label or container at hand.

INGESTION: Do NOT induce vomiting. Call a Poison Centre or doctor immediately for advice. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

INHALATION: Move person to fresh air and keep warm and at rest until recovered. Ensure those providing assistance are not exposed to vapour hazard. If respiratory irritation, dizziness, nausea or unconsciousness occurs, get immediate medical assistance. If breathing is difficult or has stopped, used mechanical device or mouth to mouth resuscitation. **SKIN:** Remove immediately all contaminated clothing and footwear. Wash affected area with plenty of soap and water. If skin irritation occurs, get medical advice. Wash contaminated clothing/footwear before re-use. **EYES:** Hold eyes open and rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do after the first 5 minutes. Continue rinsing for at least 15 minutes. Get medical attention if irritation persists.

NOTES TO PHYSICIAN: Treat symptomatically. Risk of aspiration into lungs resulting in chemical pneumonitis which may be fatal. This product or a component, may be associated with cardiac sensitization following very high exposures (well above occupational exposure limits) or with concurrent exposure to high stress levels or heart stimulating substances like epinephrine. Administration of such substances should be avoided.

SECTION 5. FIREFIGHTING MEASURES

FLASH POINT: -5 0 C

FLAMMABLE LIMITS: LFL: 1.85% v/v UFL: 11.5 % v/v

EXTINGUISHING MEDIA: Use dry chemical powder, carbon dioxide, sand or earth for small fires only. Use water fog or mist or alcohol-resistant foam for large fires. Do NOT use water in a jet. Use water spray to disperse vapours.

FIRE & EXPLOSION HAZARDS: Above flash point, vapour-air mixtures are explosive within the flammable limits given above. Vapour is heavier than air and may travel across ground and reach remote ignition sources causing a flashback fire danger. Avoid breathing smoke. Prevent extinguishing water from getting into the aquatic environment.

SPECIFIC HAZARDS: Cool fire exposed containers with large quantities of water.

FIRE-FIGHTING EQUIPMENT: Wear personal protection equipment and in enclosed spaces, self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

SPILLS: Highly flammable liquid. Vapour forms explosive mixture with air. Isolate hazard area and keep unnecessary and unprotected people away from area. Stay upwind and keep out of low lying areas. Wear appropriate personal protective equipment. Avoid contact with skin and eyes. Shut off leak if safe to do so. Remove or isolate ignition sources. Contain spill. Avoid run off into drains or sewers. Do not contaminate watercourses or the ground. Take precautions against static discharge. Bond or ground (earth) all equipment. Ventilate contaminated area. For small spills, absorb with an appropriate material, e.g. vermiculite, and dispose of waste safely in a labelled sealed container for recovery or disposal. For large spills (more than a drum), recover liquid and transfer by mechanical means to labeled salvage tank that can be sealed for recovery or disposal of product. Allow residues to evaporate. Water can be used to disperse vapors and to clean spill area although prevent water from entering sewers or drains. Remove any contaminated soil and dispose of safely by waste management company. Large spills to waterways will require specific actions such as containment booms and removal of product from surface of water. Seek advice of specialist. If contamination of drains, sewers or waterways occurs immediately notify Emergency Services (111). DISPOSAL: Dispose of contaminated waste or product to an approved enclosed controlled burner or incinerator, or to hazardous landfill in accordance with local regulations.

SECTION 7. HANDLING AND STORAGE

HANDLING: Read label before use. Use only in well-ventilated areas. Avoid breathing vapors or direct contact with product. Remove ignition sources. Avoid sparks. Electrostatic charge may be generated during pumping with risk of fire. Restrict line viscosity to avoid generation of electrostatic discharge. Take precautions to use bonded or grounded (earthed) equipment. No Smoking. Do not use compressed air for filling, discharging or handling. Keep container closed when not in use. Wear personal protective equipment to prevent breathing of and contact with product. Wear suitable chemical resistant gloves and protect eyes from splashes. Wash hands and exposed skin after handling.

STORAGE: Ensure all storage areas have adequate fire-fighting equipment. Store in closed original container in a secure cool dry well-ventilated place, away from sunlight, ignition sources, heat, oxidizing agents, and out of reach of children, and away from food, drink and animal foodstuffs. Take precautions to avoid accumulation of vapours in pits and confined spaces.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Use only in a well-ventilated area. A half-face filter mask suitable for organic gases and vapors (Type A filter material) may be suitable for low concentration level exposures. Otherwise, use full-piece organic vapour respiratory protective equipment. Where air-filtering respirators are unsuitable (e.g. air-borne concentrations are high, risk or oxygen deficiency, confined space) use positive pressure breathing apparatus.

PERSONAL PROTECTIVE EQUIPMENT (PPE): Wear impervious antistatic protective clothing including safety shoes or boots. Wear appropriate chemical resistant gloves, e.g. nitrile, PVA. Avoid contact with eyes. Wear chemical goggles or safety glasses with side shields, if splash or aerosol/mist exposure risk. Refer to the relevant AS/NZ standards for appropriate personal protective equipment. Routinely wash work clothing and protective equipment to remove contaminants. Discard any protective equipment, clothing or footwear that cannot be cleaned.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Pink

Odour: Fruity

Boiling point (0 C): 77.1

Flash point (0 C): -5

Vapour pressure (kPa): 98.3@ 200 C Density at 200 C, g/cc: 0.900

Solubility in water: 64000 mg/l pH: Not applicable

Vapour density (air =1): 3.04

Evaporation rate (nBuAc =1): 4.5

SECTION 10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID): Stable under normal storage and use conditions.

Avoid heat, sparks, open flames, ignition sources and contact with incompatible materials.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidising agents, aldehydes, nitric acid, perchloric acid. Violently reacts with potassium-tert-butoxide.

HAZARDOUS DECOMPOSITION PRODUCTS: Dependent on conditions under which decomposition occurs. No decomposition at ambient temperatures.

HAZARDOUS POLYMERIZATION: Not known to occur.

SECTION 11. TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS: This section includes possible adverse effects, which might occur if this product is not handled in the recommended manner.

INGESTION: Harmful if swallowed. Symptoms may be abdominal pain and nausea. Aspiration into the lungs can cause chemical pneumonitis which can be fatal.

INHALATION: May cause irritation of upper respiratory tract. Symptoms of overexposure include headache, dizziness, nausea, shortness of breath and vomiting. May cause central nervous system depression and unconsciousness at high concentrations.

SKIN CONTACT: Moderately irritating to skin with symptoms of redness, itching and pain. Prolonged contact may defat the skin, and result in dermatitis.

EYE CONTACT: Vapours can cause eye irritation. Direct contact, e.g. splashes, cause severe pain and irritation.

SYSTEMIC (OTHER TARGET ORGAN) EFFECTS: Animal studies indicate chronic exposures may affect the liver and kidneys. Persons with pre-existing skin disorders, eye problems, impaired respiratory function or central nervous system conditions, may be more susceptible to the effects of this substance.

CANCER INFORMATION: Not classified as carcinogen.

TERATOLOGY (BIRTH DEFECTS) AND REPRODUCTIVE DEFECTS: Not classified.

MUTAGENICITY (EFFECTS ON GENETIC MATERIAL): Not a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE: This product has been classified as being toxic to terrestrial vertebrates. Methyl isobutyl ketone has low toxicity to fish and aquatic organisms.

MOVEMENT AND PARTITIONING: Product has some solubility in water. If released into soil there is potential to leach into groundwater. There is a minimal tendency to bind to soil and sediment.

DEGRADATION AND PERSISTENCE: Not expected to bio accumulate significantly and is expected to be readily biodegradable. In air is expected to rapidly degrade in air.

ECOTOXICOLOGY: No EEL has been set for this substance.

SECTION 13. DISPOSAL CONSIDERATIONS

Recover and recycle product whenever possible. Dispose of waste in accordance with Regional Authority or local council bylaws. Ensure empty containers are vented and dry. Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums. Send clean dry drums to recycler or metal scrap reclaimer. Do not use empty drums for storing other products.

SECTION 14. TRANSPORT INFORMATION

DOT (49 CFR 172) Proper Shipping Name: Non Acetone Nail Polish Remover
UN1993, Flammable liquids, n.o.s.,(ethyl acetate, isopropyl alcohol),
Identification # UN1993
Marine Pollutant:
No Special Provisions: T8, T31
Emergency Response Guidebook (ERG) # 128 IATA (DRG)
Proper Shipping Name:
UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl alcohol), 3, PGII
Class or Division: 3
UN or ID Number: UN1993 Packaging Instructions:
Emergency Response Guidance (ICAO) #: IMO (IMDG)
Proper Shipping Name: UN1993, Flammable liquids, n.o.s., (ethyl acetate, isopropyl
alcohol), 3, PGII
Class or Division: 3.2
UN or ID Number UN1993
Special Provisions & Stowage/Segregation None Emergency Schedule (EmS) #: Other
Information Flash Point=20°C

SECTION 15. REGULATORY INFORMATION

Classified as hazardous under the HSNO Act 1996 according to criteria of Minimum Degrees of Hazard (Threshold) Regulations, 2001. EPA New Zealand Approval Code: HSR001141; Refer to Section 2 for hazardous classifications and to www.epa.govt.nz for Controls and Conditions.

SECTION 16. OTHER INFORMATION

ISSUE DATE: 25 th June 2014 REPLACES: SDS dated 1 August 2006 REASONS FOR
ISSUE: NZ Format SDS. ABBREVIATIONS: CAS No. Chemical Abstracts Service Number
EPA Environmental Risk Management Authority HSNO Hazardous Substances & New
Organisms STEL Short Term Exposure Limit TWA Time Weighted Average WES Workplace
Exposure Standard Product name: ETHYL ACETATE Date of Issue: 25 June, 2014 Review by:
June, 2019 Page 8 of 8 REFERENCES: Chemical Classification and Information database;
www.epa.govt.nz Supplier Safety Data Sheet