sinm

SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 200158 EC Standards

SDS Revision Date: 01/05/2021

Page 1 of 7

SECTION 1 PRODUCT IDENTIFICATION **Product Name: Nail Lacquer Chemical Name: Solvent Mixture** Trade No.: SKU: PCII-00595 Synonyms: Nitrocellulose Nail Lacquer **PRO TECH TOP COAT** Trade Name: INM Product Use: Cosmetic Use Only Manufacturer's Name & Address: INM 1517 Harmony Cir Anaheim , California 92337 USA Phone (714) 779-9889 New Zealand Importer Name & Address: NAILX Beauty Supplies, 5/201 Opawa Road, Hillsborough 0800 262459 Emergency Phone: Karen Clark 021 286 4077 National Poisons Centre – 0800 POISON (764 766) **SECTION 2** HAZARDS IDENTIFICATION GHSO2 FLAME HAZARD IDENTIFICATION: This product is classified as a hazardous substance and as dangerous goods according to the classification criteria of (OSHA HazCom2012 (29 CFR 1910.1200) standard Signal Word- DANGER - HIGHLY FLAMMABLE LIQUID AND VAPOR, MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. GHSO2 FLAME. GHS07-IRRITIANT Classification: Flam .Liq. 2 : Skin Sens. 1A,1B; Eye Irrit. 2A; STOT SE 3 Hazard Statements : -(H): H225 -Highly flammable liquid and vapor. H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H 335 May cause respiratory irritation. H336 - May cause drowsiness or dizziness. Physical State: Liquid / Appearance: Liquid Precautionary Statements (P): P210 - Keep away from heat/sparks/open flame/hot surfaces- No Smoking, P233 Keep container tightly closed, P243 - Take precautionary measures against static GHS07-Irritiant discharge. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P264 - Wash exposed skin areas thoroughly with soap and water after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P280 - Wear protective gloves/eye protection/face protection. P302+P352 - IF ON SKIN: Wash with soap and water. P305+P351+P338 - IF IN EYES: Rinse continuously with water several minutes. Remove contact lenses if present and can easily be removed - continue rinsing. P333+P313 -If skin irritation or rash occurs - Get medical advice/attention. P321 - For specific first aid treatment (see section 4 of this SDS). P363 - Wash contaminated clothing before reuse. P370+P378 - In case of fire, CO2, Halon (if permitted), dry chemical, or foam for extinction. P403+P235 - Store in a wellventilated place. Keep cool. P501 -Dispose of contents/container to a licensed treatment, storage or disposal facility (TSDF). Dispose according to local, state and federal regulations. **EFFECTS OF EXPOSURE:** Ingestion: If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression. Eye Contact: Irritating to the eyes. Symptoms of overexposure may include redness, itching, irritation and watering.

Skin Contact: May be irritating to skin in some sensitive individuals, especially after repeated and prolonged contact.

Inhalation: Vapors may be slightly irritating to the nose, throat and other respiratory system. Symptoms of overexposure can include nasal congestion, coughing, difficulty breathing. Inhalation of vapors exceeding the recommended levels (See section 3) can cause central nervous system depression (i.g. headaches, nausea, drowsiness or dizziness).

<u>SYMPTOMS OF OVEREXPOSURE</u>: Symptoms of skin exposure on individuals may include itching, irritation and redness.

<u>ACUTE HEALTH EFFECTS</u>: Mild or moderate irritation to eyes and skin. And high concentrations of vapors can cause headaches, nausea, dizziness or drowsiness.

CHRONIC HEALTH EFFECTS: None known.

sinm				SA	FE	ΤY	D	ΑΤ	A S	HE	ET		
SAFETY DATA SHEET Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 200158 EC Standards Page 2 of 7						,							
SECTION 3 COMPOSITION & INGREDIENT INFORMATION													
			EXPOSURE LIMITS IN AIR (mg/m³) / ppm										
					AC	CGIH		NOHSC	;		OSHA		
Chemical Names(s)	CAS No.	EINECS No.	RTECS No.	%	TLV	STEL	TWA	STEL	PEAK	PEL	STEL	IDLH	OTHER
ETHYL ACETATE	141-78-6	205-500-4	AH5425000	26-32	400	400	200	400	NF	NA	NA	2000	400 TWA / Flammable 3, STOT SE 3, Eye Irritant., H225, H319,,H336
BUTYL ACETATE	123-86-4	204-658-1	AF7350000	22-28	150	200	150	200	NF	200	200	1700	IOD NIDSH / Flammable 3, STOT SE 3, H226,H336
NITROCELLULOSE	9004-70-0	NA	QW0970000	19-23	400	400	400	200	NF	NA	NA	2000	400 TWA / Flammable 3. H225
ADIPIC ACID/NEOPENTYL Glycol/trimellitic Anhydride Copolymer	28407-73-0	NA	NA	9-12	NA	NA	NF	NF	NF	NA	NA	NA	Skin Sens. 1, H317
ACETYL TRIBUTYL Citrate	77-90-7	201-067-0	NA	6-7	NA	NA	NF	NF	NF	NA	NA	NA	Flammable Gas I, Muta. IB,Carc. IB, H220, H340,H350,
ISOPROPYL ALCOHOL	67-63-0	200-661-7	NT8050000	2-4	400	500	400	500	NF	400	500	2000	400 TWA / Flammable 3, Skin Irrit., Eye Irrit., STOT SE, H225, H316, H319
TRIMETHYLPENTANEDIYL DIBENZDATE	68052-23-3	268-316-3	NA	1-2	NA	NA	NF	NF	NF	NA	NA	NA	NA
POLYVINYL BUTYRAL	63148-65-2	NA	TR49550000	1-2	NA	NA	NF	NF	NF	NA	NA	NA	NA
EQUISETUM ARVENSE (Horsetal) extract	71011-23-9	275-123-8	NA	<	NA	NA	NF	NF	NF	NA	NA	NA	NA
BENZOPHENONE-1	131-56-6	205-029-4	DJ0700000	<0.75	NA	NA	NF	NF	NF	NA	NA	NA	NA
RED 17 (Cl 261000)	85-86-9	201-638-4	QK4250000	<1	NA	NA	NF	NF	NF	NA	NA	NA	NDSL-Warning : Do not use in or around the area of the eye, mouth or nose.

VIOLET 2 81-48-1	201-353-5	CB7700000	<1	NA	NA	NF	NF	NF	NA	NA	NA	NA
(CI 60725)												

|--|

	II SAFEIY	DATA	SH	EEI			
Prepared to OSHA, ACC, AN	SI, NOHSC, WHMIS & 200158 EC Standards			Page 3 of 7			
SECTION 4	FIRST AID MEASURES						
FIRST AID:							
Ingestion: If ingested, do no	ot induce vomiting. If product has been swallowed	d, drink plenty of v	vater or m	ilk IMMEDIATELY. If vomiting,			
continue to offer water or milk	, never give liquid to an unconscious person. Con	tact the Poison Co	ntrol Cent	er or local emergency number.			
Provide information regarding	quantity ingested and estimated time in which th	e material was ing	ested.				
Eye Contact: If the material ge	ts in the eyes, flush with plenty and sufficient amo	ount of lukewarm	water for a	at least 15 minutes. If irritation			
occurs, contact a physician or l	ocal emergency number.						
Skin Contact: If product is on t	he skin and irritation occurs, rinse thoroughly wit	h lukewarm water	; followed	by a thorough washing with soap	р		
and water on the affected area	 If redness, irritation or swelling occurs, contact 	a physician IMME	DIATELY.				
Inhalation: Remove person to	fresh air at once. If difficulty breathing, contact lo	cal emergency nu	mber or pl	hysician.			
MEDICAL CONDITIONS AGGRA			1	HEALTH			
	kin conditions and disorders of the target organs (eyes, s	kin and	3 FLAMMABILITY				
respiratory system).			0	PHYSICAL HAZARDS			
			В	PERSONAL PROTECTIO			
SECTION 5		HTING MEASU	JRES		_		
FIRE & EXPLOSION HAZA							
	ELIQUID AND VAPOR. Keep away from heat, lit cigare	ettes, sparks and ope	en				
flame. Keep container closed.				3			
Extinguishing Method: - CO ² , H	alon (if permitted), dry chemical, or foam.						
	naterial is a Class IB flammable liquid. With fire exposur						
	e carbon oxides. Vapors of this material are heavier that	•	to a				
•	a open or leaking container. First responders should w			\backslash			
•	CBA and full protective equipment. Use a water spray c	or tog to reduce direc	t	V			
•	e in extinguishing a fire involved with this material.						
Hazardouc Identification Num	har: 22 / HazCham Cada: 2(V) E						

Hazardous Identification Number: 33 / HazChem Code: 3(Y) E

ACCIDENTAL RELEASE MEASURES

SPILLS:

SECTION 6

Sinm

Appropriate personal protective equipment must be worn before and individual(s) involved in a spill cleanup can proceed.

Small Spills (< 1 gallon): Appropriate personal protective equipment for small spill falls under caption rating - B (goggles and gloves).

Maximize the ventilation by opening doors and windows and insure that you secure all sources of possible ignition. Use absorbent material to remove spill and discard absorbent material into appropriate closed container for disposal. Dispose properly in accordance to local, state and federal regulations. Wash all spill affected areas and if applicable the outside of container with plenty of soap with lukewarm water. Remove any contaminated clothing and wash thoroughly before reuse.

Large Spills (≥ 1 gallon): Appropriate personal protective equipment for large spill falls under caption rating - H (goggles, gloves, apron,

vapor mask).

Do not allow unprotected individuals to assist and/or in the immediate vicinity area of spill. Dike and contain the spill with inert material such as sand. Use only non-sparking tools for cleanup. Transfer liquid to containers for

disposal. Gather all dike material for disposal and place in appropriate disposal containers. Dispose properly in accordance to local, state and federal regulations. Wash all spill affected areas. Remove any contaminated clothing and wash thoroughly before reuse. If applicable wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of the municipal sewers and open bodies (streams, lakes, etc) water.



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 200158 EC Standards

Page 4 of 7

29 CFR₴

1910.134

HANDLING AND STORAGE INFORMATION

SECTION 7 WORK PRACTICES:

Use in a well ventilated location with appropriate exhaust ventilation and/or fans. Avoid prolonged contact and breathing vapors of this material. After use, wash hands and exposed skin with soap and water. Do not drink, eat or smoke while handling this material.

STORAGE & HANDLING:

Keep material away from open flame, heat and sparks. Open containers slowly on a secure level surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of material, therefore empty containers should be handled with safety. Store containers in a cool, dry location, away from direct sunlight, other light sources and intense heat. Store away from incompatible materials (described in section 10)

SPECIAL PRECAUTIONS:

Open containers slowly on a secure level surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of material, therefore empty containers should be handled with safety.

SECTION 8

EXPOSURE CONTROLS AND PERSONAL PROTECTION

VENTILATION & ENGINEERING CONTROLS:

When working with large quantities of this material, provide adequate ventilation (local exhaust ventilation, fans). Ensure that an eyewash station, washbasin or sink is available in the event of exposure to eyes.

RESPIRATORY PROTECTION:

No special respiratory protection is required under typical handling of material. In circumstances where vapors or sprays of this material are generated and respiratory protection is required, use only personal protection authorized by 29 CFR ₹ 1910.134, applicable U.S. State regulations or the Canadian CAS Standard Z94.4-03 and applicable standards of Canadian Provinces, EC member States, or Australia.

EYE PROTECTION:

Wear protective eyewear (safety glasses with side-shield) at all times when handling this material. Always use protective eyewear when cleaning spills. Contact lenses pose a hazard; soft contact lenses may absorb and concentrate irritants.

HAND PROTECTION:

AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. Wear protective gloves if repeated or prolonged skin contact is anticipated during handling of the material. If handling for routine industrial use, it is necessary to refer to U.S. OSHA 29 CFR ₹1910.138 for the appropriate standards of Canada, of the EC member states.

BODY ROTECTION:

AVOID SKIN CONTACT DUE TO SENSITIZING POTENTIAL. No special body protection is required under typical handling of this material. If required, refer to appropriate standards for U.S. OSHA, Canada, & EC member states.

SECTION 9	PHYSICAL & CHEMICAL PROPERTIES
APPEARANCE	Viscous liquid, various colors
ODOR	Ester (fruity) odor
ODOR THRESHOLD	Typical Acetate Characteristic
PH	Anhydrous Formula, Not Applicable
MELTING/FREEZE POINT	NA
BOILING POINT RANGE	77-130°C
FLASHPOINT	- 5°C
UPPER/LOWER	
FLAMMABILITY LIMITS	NA
VAPOR PRESSURE (50°C)	Between 175 kPa and 300 kPa inclusive
VAPOR DENSITY	ND
RELATIVE DENSITY	0.98 - 1.0
WATER SOLUBILITY	Nil - Insoluble
VISCOSITY	2,400 -3,600 cps
SOLID CONTENT	29.5 - 31.5
SOLVENT SOLUBILITY	Completely Soluble (Ketone, ester)



SAFETY DATA SHEET

STABILITY & REACTIVITY

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 200158 EC Standards

Page 5 of 7

STABILITY:

Stable under ambient temperatures when stored properly (See Section 7).

HAZARDOUS DECOMPOSITION-CONDITIONS/MATERIALS:

If exposed to extremely high temperatures the effects of thermal decomposition may include irritating vapors, carbon oxide gases (CO,CO²)

HAZARDOUS POLYMERIZATION:

May occur if exposed to extremely high temperatures.

CONDITIONS TO AVOID:

SECTION 10

High temperatures, direct sunlight, sources of heat and incompatible materials.

INCOMPATIBLE SUBSTANCES:

This material is incompatible with strong oxidizers (peroxides, superoxide's) strong acids (hydrochloric or muriatic acids) nitrates, or strong bases (lye, potassium hydroxide).

SECTION 11		TOXICOLOGICAL INFORMATIO	N				
ROUTES OF ENTRY	Inhalation - YES	Ingestion: YES	Absorption: YES				
TOXICITY DATA	This material has NOT been tested on animals t obtain toxicology data. Toxicology data available and found in scientific literature for this material is presented below.						
	Ethyl Acetate: ORAL (LD50): Acute: 5620 mg/kg [Rat]. 4100 mg/kg [Mouse]. 4935 mg/kg [Rabbit]. VAPOR (LC50): Acute: 45000 mg/m 3 hours [Mouse]. 16000 ppm 6 hours [Rat].						
TOXICITY-ACUTE	See section 2						
TOXICITY-CHRONIC	See section 2						
CARCINOGEN-SUSPECTED	This material contains Ethyl A	cetate and Isopropyl Alcohol which are not carcinogenic	to humans, but they are listed as Group				
	3 carcinogens by the IARC.						
TOXICITY-REPRODUCTIVE	This material is not reported to	cause reproductive toxicity in humans.					
TOXICITY- MUTAGENICITY	This material is not reported to	p produce mutagenic effects in humans.					
EMBRYOTOXICITY	This material is not reported to	produce embryo toxic effects in humans.					
TOXICITY-TERATOGENICITY	This material is not reported to	o cause teratogenic effects in humans.					
MATERIAL-IRRITANCY	See section 2						
BIOLOGICAL EXPOSURE INDICES	NE						
RECOMMENDATIONS-PHYSICIAN	Treat symptomatically						
SECTION 12		ECOLOGICAL INFORMATION					

ENVIRONMENTAL STABILITY:

The components in this material will slowly degrade over time into a variety of organic compounds. Specific environmental data available and found for this material are as follows.

Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bio-concentration factor = 4-14. Bio-concentration is not anticipated to be significant. This material can be removed from contaminated environments from volatilization and biodegradation. This component half-life is 6.1 hours. Butyl Acetate: Koc = 1.82. Water solubility: 120 parts $H_2O @ 25^{\circ}C (77^{\circ}F)$. Bio-concentration factor = 4.-14. Bio-concentration is not anticipated to be significant. This material can be removed from contaminated environments from volatilization and biodegradation. This component half-life is 6.1 hours.

Isopropyl Alcohol: Log Kow = 0.05-0.14. Isopropyl occurs naturally, generated during microbial degradation of plant and animal waste. Release to land or water, it will volatilize & biodegrade. Estimated half-life in water 5.4 days. Isopropyl Alcohol is not expected to bioconcentrate.

EFFECTS ON PLANTS & ANIMALS:

There are no specific data available for this product.

EFFECTS ON AQUATIC LIFE:

There are no specific data available for this product, however extremely large releases of this material may be harmful or fatal to overexposed aquatic life.

SECTION 13

DISPOSAL INFORMATION

WASTE DISPOSAL:

Waste disposal must be in accordance with appropriate Federal, State and local regulations.

SPECIAL CONSIDERATIONS:

U.S. EPA Waste number D001 (characteristic-ignitable).

sinm

SAFETY DATA SHEET

S) ININ.	SAFETY DATA SHEET							
•	CC, ANSI, NOHSC, WHMIS & 200158 EC Standards Page 6 of	7						
SECTION 14	TRANSPORTATION INFORMATION							
	, proper shipping name, hazard class, division & packaging group) is shown for each mode of transportation. Addition I by 49 CFR, IATA/CAO, IMDG and CTDGR.	ai descriptive						
49 CFR (GND)	1263, PAINT, 3 II, LTD (IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D-until 01/01/2021							
IATA (AIR)	D,CONSUMER COMMODITY,9,(IP VOL ≤ 0.5L) UN 1263, PAINT, 3, II (IP VOL ≤ 1.0 L)							
IMDG (OCN)	UN 1263, PAINT, 3 II, LTD QTY (IP VOL ≤ 1.0 L)							
TDGR (Canadian GND)	UN 1263, PAINT, 3, II, LTD QTY (IP VOL \leq 1.0 L) or "LIMITED QUANTITY" or "QUANTITE" or "LTD QTY" or "QUANT LTEE" (\leq 1.0 L)	> 						
ADR/RID (EU)	63, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L)							
SCT (MEXICO)	UN 1263, PINTURA, 3, II, CANTIDAD LIMITADA (IP VOL ≤ 1.0 L)							
ADGR (AUSTRLIA)	UN 1263, PAINT, 3, II, LTD QTY (IP VOL ≤ 1.0 L)							
* This product may also be	shipped as an Excepted Quantity (Inner Package Volume ≤ 30 mL, Total Quantity ≤ 500 mL per Outer Package)							
SECTION 15	REGULATORY INFORMATION							
New Zealand HSNO Appr Code	oval HSR02552							
SARA Reporting Requiren	This product contains Isopropanol a substance subject to SARA Title III, section 313 reporting requirements. contains Ethyl Acetate a substance that is subject to SARA Title III, section 304 reporting.	. This product						
SARA Threshold Planni Quantity	There are no specific Threshold Planning Quantities for the components of this product.							
TSCA Inventory Statu	The components of this product are listed on the TSCA Inventory.							
CERCLA Reportable Qua (RQ)	Ethyl Acetate 2,270 kg (5,000 lbs.) Butyl Acetate 2,270 kg (5,000 lbs.)							
Other Federal Requireme	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapt	ter G (Cosmetics)						
Other Canadian Regulati	This product has been classified according to the hazard criteria of the CPR and the Safety Data Sheet contains all the information required by CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D2B (Flammable Liquid, Other Toxic Effects) Red 17- NDSL- Warning : Do not use in or around the area of the eye, mouth or nose	T						
State Regulatory Informatio	 Butyl Acetate is found on the following state criteria lists; California OSHA Hazardous Substances List (CA), Quality Management List (DE), Massachusetts Hazardous Substances List (MA), New Jersey Right-to Know York List of Hazardous Substances (NY), Pennsylvania Right-to-Know List (PA), and Washington Permissible for Air Contaminants (WA), Wisconsin Hazardous Substances List (WI). Ethyl Acetate is found on the following state criteria lists; CA, DE, MA, MN, NJ, NY, PA, and WA. Isopropanol is found on the following state criteria lists; CA, MA, MN, NJ, PA and WA. Nitrocellulose is found on the following state criteria lists; DE, MA and PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the foll criteria lists; California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Sub (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Ha Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (WY), Penn Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). 	List (NJ), New e Exposures List lowing state ostances List izardous						
Other Requirements	The primary components of this material are listed in Annex I of EU Directive 67/548/EEC Ethyl Acetate: Flammable (F) Risk Phrases (R): 11-36/37/38 - Highly flammable. Irritating to eyes, respiratory system and skin. Safety Phrases: (S): 2-16-23-29-33. KEEP OUT OF REACH OF CHILDREN. Keep away from sources of ignition - No Smoking. Do not breathe gas, fumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges. Butyl Acetate: Flammable (F) Risk Phrases (R): Flammable Safety Phrases (S): 9-16-33 - Keep container in a well ventilated area. Keep away from sources of ignition - No Smoking. Take precautionary measures against static discharges. Isopropanol: Flammable (F) Risk Phrases (R): 11-36/37 - Highly flammable, Irritating to eyes and respiratory system. Safety Phrases (S): 2-7-16-24/25/26 - KEEP OUT OF REACH OF CHILDEREN. Keep container tightly closed. Avoid contact with the skin and eyes. In case of contact with eyes, rinse immediately with sufficient water and seek medical attention or advice.							

advice.



SAFETY DATA SHEET

Prepared to OSHA, ACC, A	Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 200158 EC Standards Page 7 of 7						
SECTION 16	OTHER INFORMATION						
Other Information	DANGER! HIGHLY FLAMMABLE LIQUID AND VAPO SERIOUS EY IRRITATION. MAY CAUSE RESPIRATO Keep away from heat/sparks/open flame/ hot surfaces - measures against static discharge. Avoid breathing fur and water after handling. Avoid eye contact. Wear prote ON SKIN: Wash thoroughly with soap and water. IF IN E Remove contact lenses if present and can easily be Get medical advice or attention. Store in a well-ve OUT OF REACH OF CHILDREN	RY IRRITATION. MAY CAUSE DRC No Smoking - Keep container tightly le/mist/vapors/sprays. Wash exposed ctive equipment; protective gloves/e EYES: Rinse continuously with lukew e removed - continue rinsing. If s	DWSINESS OR DIZZINESS. closed. Take precautionary d skin areas thoroughly with soap yes, protective/face protection. IF arm water for several minutes. kin irritation or rash occurs -				
Definitions & Terms	SEE Final (Separate) SDS Page -Following the Safety	Data Sheet					
DISCLAIMER	This Safety Data Sheet is offered pursuant to OSHA's H government regulations must be reviewed for applicably information contained herein is accurate as of this date; guaranteed and no warranties of any type, either express consequences of its use The information contained here with other materials all component properties must be co questions regarding the proper interpretation of these sh speak with your physician.	of the material. To the best of Cosm however accuracy, representation, s used or implied are provided to purcha- in relates only to the specific product posidered. Use these materials only a	etic Industries knowledge the uitability or completeness is not aser's intended purpose or for t(s). If this product(s) is combined as directed. If you have any				